



EXTREME ENVIRONMENTS NEED TOUGH BEARINGS.

MOUNTED SPHERICAL SOLID BLOCK UNITS & SPLIT BLOCK HOUSED UNITS.

When you're up against harsh environments, you need a resilient and reliable roller bearing housed unit that can stand up to tough conditions. RBI Bearing's line of Mounted Spherical Units are designed to withstand challenging environmental conditions, such as, impacts from aggregate, extreme temperatures, heavy load conditions and misalignment. Our Mounted Spherical Units are also available with Armor Bearing Technology & Protection to reduce bearing friction and substantially increase bearing life.



SPHERICAL ROLLER BEARING SOLID BLOCK HOUSED UNITS

- Steel housing
- Powder coated housing (other coatings available)
- Field convertible from non-expansion to expansion (vice versa)
- Bearing insert pressed steel retainers
- Bearing rings & roller 52100 bearing steel
- Ulti-plex synthetic grease
- Teflon labyrinth seal
- Concentric locking collar
- Size range: 1-15/16" 4-15/16"
- Bore sizes over 4" come with a double collar
- Housing dimensions match both Type-E & traditional straight bore units
- Housings machined at each end for easier installation
- Interchangeable with most major brands
- Handles misalignment up to ±1.5 degrees
- High load capacity
- · Purge relief valve
- Zerk fitting

SPHERICAL ROLLER BEARING SPLIT BLOCK HOUSED UNITS

- Cast Iron
- 52100 bearing steel with Brass cage
- C3 clearance, oil groove & lube holes, other clearances available upon request
- Aluminum Seal
- HA adapter assembly consists of Sleeve, Nut & Washer and is interchangeable with SNW adapter assembly
- Pillow block assembly uses either 2 seals or 1 seal & 1 end cover
- Other sizes and dimensions available upon request











SPHERICAL ROLLER BEARING SOLID BLOCK HOUSED UNITS



Part Number	Bore Size	A	В	E (min)	E (max)	F	G	Н	J (Bolt Size)	u	Weight (LBS.)
E2P115	1.938	2.250	4.50	6.00	7.25	8.86	2.24	1.22	5/8	3.00	14
E2P203	2.188	2.500	5.00	6.50	8.00	9.63	2.36	1.22	5/8	3.18	18
E2P207	2.437	2.750	5.50	6.88	8.74	10.24	2.80	1.38	5/8	3.52	23
E2P215	2.938	3.125	6.25	7.88	9.76	11.75	2.92	1.38	3/4	3.84	30
E2P307	3.438	3.750	7.50	9.38	11.50	13.74	3.50	1.85	7/8	4.34	45

STRAIGHT BORE DIMENSIONS - 2 BOLT





Part Number	Bore Size	A	В	E (min)	E (max)	F	G	Н	J (Bolt Size)	LI .	Weight (LBS.)
T2P115	1.938	2.250	4.50	5.94	6.56	8.13	2.24	1.22	5/8	3.00	14
T2P203	2.188	2.500	5.00	6.50	7.06	8.87	2.36	1.22	5/8	3.18	18
T2P207	2.437	2.750	5.50	6.81	7.44	9.25	2.80	1.38	5/8	3.52	23
T2P215	2.938	3.250	6.37	7.72	8.43	10.44	2.92	1.38	3/4	3.84	30
T2P307	3.438	3.750	7.50	9.25	10.75	13.00	3.50	1.85	7/8	4.34	45

ALSO AVAILABLE WITH ARMOR BEARING TECHNOLOGY & PROTECTION. CALL 1-800-708-2128 FOR MORE INFORMATION AND PRICING.



TYPE E DIMENSIONS - 4 BOLT







T4P307

Part Number	Bore Size	A	В	D	E (min)	E (max)	F	G	Н	J (Bolt Size)	L1	Weight (LBS.)
E4P307	3.438	3.750	7.50	2.38	9.25	11.25	13.623	3.74	1.85	3/4	4.46	45

STRAIGHT BORE DIMENSIONS - 4 BOLT






ALSO AVAILABLE WITH ARMOR BEARING TECHNOLOGY & PROTECTION. CALL 1-800-708-2128 FOR MORE INFORMATION AND PRICING.




SPHERICAL ROLLER BEARING SPLIT BLOCK HOUSED UNITS



Part Number	Shaft Diameter	A	В	D	E (min)	E (max)	F	G	Н	J (Bolt Size)	L
SAF517	2-15/16	3.75	7.32	-	9.88	10.98	12.99	3.50	1.26	3/4" (2)	5.00
SAF520	3-7/16	4.50	8.74	-	11.61	13.11	15.24	4.37	1.77	1" (2)	5.98

2-BOLT Housing Part No.	SPHERICAL ROLLER Bearing P/N	ADAPTER Assembly P/N	SEAL P/N	END Cover P/N	STABILIZING Ring P/N	PILLOW BLOCK ASSEMBLY P/N
SAF517	22217CAKW33C3	HA317_2-15/16"	LER 53	A517	SR-17-14	SAF 22517
SAF520	22220CAKW33C3	HA320_3-7/16"	LER 102	A520	SR-20-17	SAF 22520



Part Number	Shaft Diameter	A	В	D	E (min)	E (max)	F	G	Н	J (Bolt Size)	l
FSAF522	3-15/16	4.94	9.65	2.75	12.64	14.49	16.50	4.76	2.01	3/4" (4)	6.50
FSAF526	4-7/16	6.00	11.50	3.25	14.65	15.98	18.39	5.12	2.40	1" (4)	7.99
FSAF528	4-15/16	6.00	11.73	3.38	15.98	17.13	20.12	5.87	2.40	1" (4)	7.64
FSAF532	5-7/16	6.69	13.31	3.75	17.40	19.25	22.01	6.26	2.64	1" (4)	8.74

4-BOLT Housing Part No.	SPHERICAL ROLLER Bearing P/N	ADAPTER Assembly P/N	SEAL P/N	END Cover P/N	STABILIZING Ring P/N	PILLOW BLOCK Assembly P/N
FSAF522	22222CAKW33C3	HA322_3-15/16"	LER 109	A522	SR-22-19	FSAF 22522
FSAF526	22226CAKW33C3	HA3126_4-7/16"	LER 117	A526	SR-26-0	FSAF 22526
FSAF528	22228CAKW33C3	HA3128_4-15/16"	LER 122	A528	SR-28-0	FSAF 22528
FSAF532	22232CAKW33C3	HA3132_5-7/16"	LER 130	A532	SR-32-0	FSAF 22532

ALSO AVAILABLE WITH ARMOR BEARING TECHNOLOGY & PROTECTION. CALL 1-800-708-2128 FOR MORE INFORMATION AND PRICING.





Should I lubricate my Mounted Roller Bearings?

YE5!



But, how you choose to grease your bearings is an important decision. It's estimated that 55% of mounted bearings fail because of lubrication problems and another 25% fail due to contamination issues. Grease purge from bearings also create safety hazards such as slips and falls, increases the risk of fires and can be considered a hazardous material. The conventional daily greasing of bearings is also a major expense, costing as much as 5X the initial cost of the bearing!

RBI Bearing has a simple solution to make your choice easy. **Armor Bearing Permanent Lubrication** - this treatment provides a permanent Polymer lubrication to the bearing that creates extra protection against contamination ingress and saves time and operation costs.

- Extends the life of your bearings by providing constant and consistent lubrication at all times
- Eliminates hazards
- No need to climb, plumb, or put an employee at risk in order to grease bearings
- · No hazardous material concerns
- Helps block debris and reduce foreign contamination

- Operates in temperatures up to 350°
- · Reduces equipment maintenance costs
- Does not drip out of the bearing and contaminate the environment
- Does not alter the dimensional tolerances of the bearing
- Environmentally friendly

OTHER ARMOR BEARING TECHNOLOGY AND PROTECTION SOLUTIONS:

Armor Nano Technology - a unique Nano technology treatment proven to reduce metal to metal friction by up to 99% and greatly extend bearing life.

Armor Coated Protection (an Enviropeel Technology) - A UV-resistant thermoplastic polymer bearing shield installed by the end user or a spray application of the thermoplastic material applied on site by a trained technician. Prolongs bearing life by up to 500%.

Fill Firmor Bearing Technology & Protection solutions have been proven to increase bearing life and drastically reduce shutdown and the need for maintenance.

CFLL 1-800-708-2128 OR EMFIL INFO@RBIBEFRNG.COM FOR MORE INFORMFTION FIND PRICING.





CORE PRODUCTS

- Ball Bearings
- Angular Contact Bearings
- Tapered Roller Bearings
- Spherical Roller Bearings
- Cylindrical Roller Bearings

- Insert Bearings
- Mounted Units
- Stainless Steel & Thermoplastic Mounted Units
- Spherical Roller Mounted Units
- Armor Bearing Technology & Protection